

PANEL CONDITION	FIRST COAT	TOPCOAT	NUMBER OF COATS	DRY FILM IN MICRON S	240 HOURS	500 HOURS	1000 HOURS	1500 HOURS	2000 HOURS	3000 HOURS	4000 HOURS
1 RUSTED 40 μ	KR PRIMEX KILLRUST	NONE	3	150 μ	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING
2 SANDBLAST PER sp5	TAMBOUR ANTIRUST	TAMBOUR EITAN	ANTIRUST 1 EITAN 2	50 μ 80 μ	NO BLISTERS XSCRATCH NO DEGRADING	NO BLISTERS HEAVY BLISTERING #8 XSCRATCH NO DEGRADING	TEST ENDED				
3 RUSTED 40 μ	AMERLOCK 400 EPOXY		1	150 μ	NO BLISTERS ASTM 714 #8 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #8 XSCRATCH NO DEGRADING	TEST ENDED				
4 RUSTED 40 μ	TAMBOUR RUSTBLOCK EPOXY		1	150 μ	NO BLISTERS ASTM 714 #8 XSCRATCH NO DEGRADING	NO BLISTERS HEAVY BLISTERING #8 XSCRATCH NO DEGRADING	TEST ENDED				
5 RUSTED 40 μ	KILLRUST 600 2 COATS	BAF 400 EPOXY	1	120 μ	NO BLISTERS XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING
6 RUSTED 40 μ	KILLRUST 600 2 COATS	AMERLOCK 400 EPOXY	1	150	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	TEST ENDED				

FIG. 1A

PANEL CONDITION	FIRST COAT	TOPCOAT	NUMBER OF COATS	DRY FILM IN MICRON S	240 HOURS	500 HOURS	1000 HOURS	1500 HOURS	2000 HOURS	3000 HOURS	4000 HOURS
7 RUSTED 40 μ	KILLRUST 60 μ 2 COATS	BAF 600 POI YURETH ANE	1	60 μ	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	TEST CONTINUING					
8 RUSTED 40 μ	KILLRUST 60 μ 2 COATS	AMERCOAT 450 S POLYURETH ANE	1	60 μ	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	TEST CONTINUING					
9 RUSTED 40 μ	KILLRUST 60 μ 2 COATS	MIRLET UNICRIL POLY. ACRYLIC	1	60 μ	NO BLISTERS ASTM 714 #10 XSCRATCH NO DEGRADING	TEST CONTINUING					
10 RUSTED 40 μ	KILLRUST 60 μ 2 COATS	MIRLET SUPERMAIL 96	2	80 μ	Z						
11 SANDBLAST SP-5	MIRLET ZINCROHATE 1 COAT 60 μ	MIRLET SUPERMAIL 96	2	60 μ	A						

FIG. 1B



FIG. 2A




FIG. 2B



FIG. 2C

卷之三




FIG. 3A




FIG. 3B




FIG. 4

5/5




FIG. 5




FIG. 6




FIG. 7

10064360 - 020402